



JITRAKOR RC

HIGH TEMPERATURE-RESISTANT, SELF-ADHESIVE, ANTI-CORROSION TAPE BASED ON PETROLATUM



TECHNICAL SPECIFICATIONS

Chemical base:	Fabric carrier impregnated with petrolatum sealing mass
Colour:	Red
Material top layer:	PVC
Minimum temperature resistance:	-30 °C
Maximum temperature resistance:	100 °C
Moisture resistance:	Very good
Thickness (mm):	1.2 mm
Water resistance:	Very good

STORAGE CONDITIONS

Shelf life: At least 24 months after production.
Limited shelf life after opening.

PRODUCT DESCRIPTION

High temperature-resistant, self-adhesive, anti-corrosive tape based on petrolatum with heat-shrunk PVC film.

FIELD OF APPLICATION

For the (mechanical) protection of, for instance, (underground) metallic conduits, connections, systems and installations. Very simple to process, extremely suitable for uneven surfaces and/or shapes. Extremely suitable for vertical conduits.

PREPARATION

Working Conditions: Apply only at temperatures between +10 °C and +45 °C.

Preliminary Surface Treatment: Apply on a dry and clean substrate. Remove loose paint traces and rust.

APPLICATION

Directions for use:

Apply under light pressure with 66% (3 layers) overlap and tool manually.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.