



KOLMAT® PLASTIC

SEALANT FOR SEALING CONICAL AND CYLINDRICAL SYNTHETIC THREADED CONNECTIONS



STORAGE CONDITIONS

Shelf life: At least 15 months after production.
 Stored in unopened packaging between +5°C and +25°C.
 Best Before Date (MM/YY): see packaging. Close packaging properly after use and store in a dry, cool, and frost-free location.
 Limited shelf life after opening.

PRODUCT DESCRIPTION

Sealant for sealing conical and cylindrical synthetic threaded connections.

FIELD OF APPLICATION

For sealing conical and cylindrical metal and synthetic threaded connections (synthetics/synthetics and synthetics/metal). Suitable for cold and warm water and (compressed) air. Suitable for, e.g., PVC, CPVC and ABS eventually in combination with copper, brass, (galvanised) steel and stainless steel.

PROPERTIES

- THF-free
- Fast
- Liquid

PREPARATION

Working Conditions: Do not use in temperatures $\leq +5^{\circ}\text{C}$.

Preliminary Surface Treatment: Clean and dry surfaces with a degreaser (Griffon PE Cleaner) and use a clean, well-absorbing, fluff-free cloth (Griffon Cleaner Cloth).

APPLICATION

Directions for use:

Apply evenly to the male part and the female part. Assemble joint immediately and remove residues. Joint is adjustable for about 5 minutes. Joint can be loaded up to 8 bar (medium 20°C) or 2 bar (medium 80°C). After curing lightly demountable.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.