



# SEALANT FINISHING SET

## PERFECT HELP FOR SMOOTHENING SEALANT JOINTS



### APPLICATION

#### Directions for use:

Spray GRIFFON Sealant Finisher or an acid-free soap-water solution over the applied sealant joint. Moisten the flat side of the GRIFFON Sealant Finishing Tool with GRIFFON Sealant Finisher. Place the flat side of the tool with the exact joint width dimension onto the joint and smoothen the sealant by pulling the Finishing Tool towards you. Note: keep the tool tight against the substrate and the wall. Wipe off the excess sealant on a cloth. Let the sealant cure according to the instructions of the respective sealant.

#### Points of attention:

- Check beforehand if the joint width is the same over its entire length.
- Smooth horizontal joints in sanitary areas at a 45-degree angle to allow water to drain properly. This prevents dirt and soap residue from being left behind, which can cause mould.
- The Sealant Finishing Tool is easy to clean with a damp cloth or GRIFFON Wipes.
- Use the small diameter of the Sealant Finishing Tool to remove excess sealant between the tile joints.

### PRODUCT DESCRIPTION

GRIFFON Sealant Finishing Set is a set of 4 different tools for smoothening all sealant joints. For beautiful, tight and very smooth joints in bathrooms, toilets, kitchens and for any other sealing application. The Finishing Tools are made of thermoplastic rubber, making them super long-lasting and easy to clean. Thanks to its small shape, the aid can also be used for sealant joints in places that are difficult to reach, such as, sinks or baths with mounted taps or shower fittings.

### FIELD OF APPLICATION

Ideal for smoothening Acrylic, Silicone, PU- and Polymer sealants. In addition, The GRIFFON Sealant Finishing Set can also be used for smoothening epoxy coatings and for glass applications, such as an aquarium or renewing the sealant of a window frame. The 4 piece set can be used for the following joints: - 45° joints in widths: 3 mm, 5 mm, 6 mm, 8 mm, 10 mm and 14 mm - Round joints in widths: 2 mm, 4 mm, 6 mm, 8 mm, 14 mm and 20 mm - Straight 90° joints - Flat joints.

### PROPERTIES

- Set of 4 tools made of thermoplastic rubber
- Multi functional: for round joints, 45° & 90° joints and flat joints
- Easy to clean – sealant residues removed easy

### PREPARATION

Tools: GRIFFON Sealant Finisher, GRIFFON Wipes

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.