



LOCK SPRAY

LUBRICATING AND MAINTENANCE AGENT FOR LOCKS



STORAGE CONDITIONS

Shelf life: At least 36 months after production.
 Stored in unopened packaging between +5°C and +25°C.
 Close packaging properly after use and store in a dry, cool, and frost-free location.
 Limited shelf life after opening.

PRODUCT DESCRIPTION

Lubricating and maintenance agent for (cylinder) locks.

FIELD OF APPLICATION

For lubrication and maintenance of, e.g. locks for (garage) doors, cars, padlocks, fences and gates. Also for immediate defrosting and preventing the freezing of locks.

PROPERTIES

- Water displacing
- Water repellent
- With precision spray hose
- Can be used in all positions

APPLICATION

Directions for use:

Shake well before use.

Spray on the lock and open and close the lock several times.

TECHNICAL SPECIFICATIONS

Chemical base:	Mineral oil products and silicones
Colour:	Green/blue
Minimum temperature resistance:	-75 °C
Maximum temperature resistance:	200 °C

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.